Inter-Tech Elektronik Handels GmbH

IPC SC-2100



IPC SC-2100

The **IPC SC-2100** is an enclosure for Mini-ITX motherboards with a dual 2.5"/ 3.5" Hot-Swap frame in the front, which is located behind a lockable front door. Another external 2.5" Hot-Swap frame is located on the back of the enclosure cage.

The standard 60mm fan ensures clean air and thus a perfect cooling behavior inside. A slot for a Flex-ATX power supply as well as a USB 2.0 and a USB 3.0 front connector complete the package.

- ✓ 2-fold 2.5"/ 3.5" Hot-Swap cage
- ✓ separate 2.5" Hot-Swap frame on the back
- ✓ lockable front door
- √ 60mm fan installed as standard



IPC SC-2100

_			
Ena	citic	3 t i A	nc
SUC	cific	auv	1113

Motherboard

Max. drive bays 2.5" or 3.5" external Hot-Swap (max. 12G): 2 2.5" external Hot-Swap: 1 Front connectors USB 3.0: USB 2.0: Cooling system Rear: 1x 60mm

(included, 3pin connector, without speed signal)

Controls Power-Button Reset-Button **LED**

1x Power-LED 1x Alert-LED1 1x HDD-LED

> 3x Network activity 2 2x HDD power/ 2x HDD activity

Power Supply Flex-ATX PSU Material 1.0mm steel Max CPU-Cooler height 40mm

Max Graphic card length

Shipping Unit: 1 Piece Packing units Packing Unit: 4 Pieces Warranty 24 Months

Article number 88887285 EAN-Code 4260455644655 Scope of Delivery Screw set

Mounting bracket for Flex-ATX PSU

Stands

Key

Mini-ITX

Tool for thumbscrews **Features**

Lockable front door

2-fold HDD hot-swap cage Separate 2.5" Hot-Swap frame on the back

USB 3.0 and USB 2.0 internally as a block connector

¹For the functionality of the alert LED the additional hardware is necessary (connectors on mainboard, fan monitoring). ²For the functionality of network activity LEDs the connectors on your mainboard are necessary.

Dimensions and Weight

	Cage	Case	Package
Height	125mm	140mm	220mm
Width	205mm	205mm	310mm
Depth	240mm	260mm	270mm
	t): 2.25kg oss): 3.80k	g	

ower Supply	<u></u>	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	_ 4
PCI-Express 6+2Pin	460	UL.
PCI-Express in	tho	
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

CE **Certification:**